

HARD MOUNTED WASHER EXTRACTORS

**RX
RANGE**

RX80	RX105	RX135	RX180	RX240	RX280	RX350	RX520
8KG 18LB	11KG 24LB	14KG 31LB	18KG 40LB	24KG 53LB	28KG 62LB	33KG 73LB	52KG 115LB



FEATURES

- Hard mounted, normal spin
- Stainless steel top panel & Anthracite grey front and side panels
- Stainless steel drum and tub
- Xcontrol - easy to use microprocessor
- Patented Soap Hopper
- High capacity water inlets (RX280)
- Large drain valve (Ø 76 mm)
- Easy access to all vital parts from the front
- Large door opening for easy loading & unloading

OPTIONS

- Xcontrol Plus - Fully programmable
- Coin operated timer (CPS)
- Stainless steel front and side panels
- USB plug (on the back panel)
- Easy Soap - liquid soaps connection
- Liquid soap pumps
- Water recovery kit
- Steam heating version
- 3rd water inlet
- High capacity water inlets (RX180, 240)



RX80

RX105

RX135

RX180

RX240

RX280

RX350

RX520

TYPE		RX80	RX105	RX135	RX180	RX240	RX280	RX350	RX520
INNERDRUM									
Maximum capacity 1:9	kg	9	12	15	20	27	32	37	58
Capacity 1:10	kg	7,5	10,5	13,5	18	24	28	33	52
Volume	litres	75	105	135	180	240	280	332	520
Diameter	mm	530	620	620	750	750	750	914	914
DRUM SPEED									
Wash	rpm	50	46	46	42	42	42	38	38
Extraction	rpm	820	760	760	490 (690)*	490 (690)*	490 (690)*	540	440
G-FACTOR									
		200	200	200	100 (standard)	100 (standard)	100 (standard)	150	100
HEATING									
Electricity (standard)	kW	6 / 9	6 / 9 / 12	9 / 12	12 / 18	18	18 / 21,9	27	40,6
Steam	bar	1 - 8	1 - 8	1 - 8	1 - 8	1 - 8	1 - 8	1 - 8	1 - 8
Hot water	°C	90	90	90	90	90	90	90	90
Sound pressure level	dB (A)	< 65	< 65	< 65	< 65	< 65	< 65	< 65	< 65
Water valves connection	BSP	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	1"
Water pressure	kPa	100-800	100-800	100-800	100-800	100-800	100-800	100-800	100-800
Rec. water pressure	kPa	300-500	300-500	300-500	300-500	300-500	300-500	300-500	300-500
Water inlet	l/min	20	20	20	20	20	20	66-188	183-518
Drain valve	outer Ø mm	76	76	76	76	76	76	2x76	2x76
Flow amount with drain valve	l/min	210	210	210	210	210	210	2x210	2x210
Steam valve connection	BSP	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	3/4"	3/4"
Steam pressure	kPa	100-800	100-800	100-800	100-800	100-800	100-800	100-800	100-800
DIMENSIONS									
Size H×W×D	mm	1115	1225	1225	1410	1410	1410	1500	1500
	mm	660	750	750	890	890	890	1060	1060
	mm	785	785	900	915	1060	1135	1030	1315
Net weight	kg	135	170	190	255 (315)*	275 (330)*	290 (355)*	410	520
TRANSPORT DATA									
Packed H×W×D	mm	1245	1355	1355	1550	1550	1550	1625	1625
	mm	710	800	800	925	925	925	1088	1088
	mm	835	835	950	970	1130	1190	1060	1345
Gross weight	kg	145	185	200	270 (335)*	290 (355)*	305 (385)*	425	535

* 200 G-Factor execution



POWERWASH

Perforated lifting ribs bring extra rinsing effect that results in lower water consumption and better washing results.

